

2-way switch 16AX 250V~ for half element with fast terminal connection system white Simon 27 Play

REF. 27211-64



BASIC INFORMATION

DESCRIPTION

White in colour, and of half an element, this 2-way switch 16 AX and 250 V belongs to the Simon 27 Play series. It is made of metal components with halogen-free thermoplastic insulation and thermoset trim. To clean properly, it is recommended to use a soft, dry cloth and avoid the use of aggressive substances containing chlorine. Tilting function and dimensions 22,5 mm x 45 mm frame Suitable for surface and flush mounting. Fast-terminals connection system. The wire that supports is from 1.5 to 2.5 mm and the stripping of the wire required to make the connection is 11 mm The lines of the new Series 27 Play are in 2 basic finishes: Ivory and white, but also allows you to exchange the rockers of the mechanisms (switches, switches, 2-way switches, etc). For this piece, it is possible to replace the finish of the supplied rocker. There are 5 additional finishes available!

FINISH

White

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with rocker

ETIM CLASS

EC001590

REMARKS

Possibility of substituting the finish of the rocker supplied with a different one. 5 additional finishes available.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

16 AX

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP21

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

Half element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Pivoting

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

CLAW

Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American, Small
spaces and Centralisations

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Suitable for surface and flush
mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053251874

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

365040

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.027

PRODUCT NET WEIGHT

0.027

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053075555

UNITS CONTAINED PACKAGING

5

PACKAGING HEIGHT

54

PACKAGING WIDTH

52

PACKAGING LENGTH

130

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.012

PACKAGING VOLUME UNIT

HLT

PACKAGING GROSS WEIGHT

0.135

PACKAGING NET WEIGHT

0.135

PACKAGING WEIGHT UNIT

KGM