Composable group of 2 IP55 10AX two-way switches with quick terminal connection system gray Simon Aqua

REF. **4400397-035**



BASIC INFORMATION

FINISH
Grey

COMPATIBILITY
Simon 27 Mechanisms

ETIM CLASS
EC001590

TECHNICAL INFORMATION

IK CLASSIFICATION
07

IP RATING
IP55

MONOBLOCK
Yes

INDICATOR FUNCTION
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

NOMINAL VOLTAGE (V~)
250 V~

CURRENT (A)
10 AX

RAL
7035

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
11

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Fast

REGULATIONS

REGULATIONS
Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018*1 | IEC 60884-1 Ed. 3.2*2 | UNE 20315-1-1:2017*2 | UNE 20315-1-2:2017*2 | EN IEC 60670-1:2021 + A11:2021*3 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.089

PRODUCT NET WEIGHT
0.089

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053298558

UNITS CONTAINED PACKAGING
5

PACKAGING HEIGHT
86

PACKAGING WIDTH
83

PACKAGING LENGTH
222

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1584636

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.445

PACKAGING WEIGHT UNIT
KGM