

## LedFlex 810.34 2700 K IP65 HE

REF. 81034100-982



### BASIC INFORMATION

#### APPLICATION

General lighting, Indoor  
decorative lighting

#### PACKAGING CONTENTS

1 unit (5m)

#### ETIM CLASS

EC002706

## TECHNICAL INFORMATION

### IP RATING

IP65

### DRIVER INCLUDED

No

### LUMENS/W

4200 lm/36W

### OPERATING TEMPERATURE RANGE (°C)

-20 - 40 °C

### L70 (°C)

30,000 h

### OPTICS

General

### COLOR TEMPERATURE (K)

2700 K

### LIGHT BEAM APERTURE ANGLE (°)

120°

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### CONTROL

PWM

### LIGHTING EFFICIENCY (LM/W)

116,7 lm/W

### POWER (W)

36 W

### CRI

80

### LUMENS (LM)

4200 lm

## INSTALLATION AND MAINTENANCE

### INSTALLATION TYPE

Hardware

## REGULATIONS

### WARRANTY

3 years

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053202623

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.424

### PRODUCT NET WEIGHT

0.424

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053202623

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

2

### PACKAGING WIDTH

24

### PACKAGING LENGTH

25

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

1200

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

424

### PACKAGING NET WEIGHT

0.424

### PACKAGING WEIGHT UNIT

GRM