

Voice and data flat plate with dust cover for 1 element and 1 RJ45 connector category 5e UTP white Simon K45

REF. KA95U/9



BASIC INFORMATION

DESCRIPTION

With the guarantee of the most impeccable workplace solutions, the flat base plate of voice and data with RJ45 connector of category 5e UTP and dust cover with 1 element Simon K45, it is designed to give the maximum functionality to your office, office or building. Manufactured with halogen-free thermoplastic, prevent the propagation of the flame and toxicity by smoke in case of fire, reaching a temperature range of installation of between -5°C and 60 ° C With finishes in Graphite, its installation can be carried out on the surface-mounted or recessed, without the need for screws to be direct snap-fit and is compatible with Keystone and cabling ports type 22-26 AWG. The flat base plate K45, with 1 and 2 RJ45 connectors, it may be combined in vertical enclosures, such as columns, Teleblock, channels mechanism-holders, using the 90° positioner (ref.K66). The collection K45 for flat voice and data plates, it is the perfect to win in functionality, workplace solutions and innovation.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Voice and data flat plate with dust cover and RJ45 category 5e UTP connector

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

IP RATING

IP20

RAL

9003

RJ45 CONNECTION

With insertion tool

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RJ45 ADAPTOR MODULE

Supplied with the voice and data plate

CONNECTOR CHARACTERISTICS

Category 5e UTP

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

NUMBER OF MODULES

Four

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.022

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

911400

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436046092

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.22

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

70

PACKAGING NET WEIGHT

0.22

UNITARY PACKAGING GROSS
WEIGHT

0.022

PACKAGING WIDTH

93

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

140