

**Customisable set with cover and brush, 3 schuko socket outlets and 3 empty elements black S400 Indesk**

REF. 44603000-138



## BASIC INFORMATION

### DESCRIPTION

Kit within the table customizable in black colour, series Simon 400 Indesk with cover and brush strip and 3 sockets for Schuko plugs and 3 empty elements. It is manual elevation and access to the cabling is done with brush strip and has dimensions of 340 x 185 x 85 mm, approximately. It is made of painted steel enclosure, profile of anodised aluminium and the covers and fastenings are manufactured in self-extinguishing thermoplastic and halogen-free, so that it is to guarantee the no-propagation of the spread in case of fire and a level of low toxicity in case of smoke. When cleaning, it is a task quite simple because just need to use a dry and soft cloth, without having to use never abrasive cloths or cleaners containing chlorine in its formulation, as it could be damaged and does not operate correctly.

### FINISH

Black

### MATERIAL

Metal

### COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

### PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

### ETIM CLASS

EC002759

### REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with brush

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

### NUMBER OF POSSIBLE ELEMENTS

3

### FORMAT

Schuko

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

### CURRENT (A)

16 A

### IP RATING

IP30


### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

### TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL

9005

### NUMBER OF REAR ENTRANCES

3

### RECESS DIMENSION (MM)

318 x 175 mm (± 2mm)

### NUMBER OF SOCKETS

3 sockets for standard current circuit

### VERSION

6 elements

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS

With brush

### CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

### REMOVAL OF COMPONENTS

### NUMBER OF COVER OPENING POSITIONS

1

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING

By lateral tightening of claws provided with the enclosure.

Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

### REMOVAL OF THE FRAME

Only with tool

### INSTALLATION TYPE

Suitable for recessed mount in furniture.

### OPENING ORIENTATION

At 45°

### REMOVAL OF THE PLATE

Only with tool

### SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD; Directiva 2011/65/UE RoHS; EN 50581:2012; EN 60670-1:2005; EN 60670-1:2005 A1:2013; IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

UNITARY EAN CODE 8421053196625	UNITARY PACKAGING WEIGHT UNIT KGM	PACKAGING MEASUREMENT UNIT MMT
UNITARY PACKAGING HEIGHT 0	PACKAGING EAN 8421053196625	PACKAGING VOLUME 6657600
UNITARY PACKAGING WIDTH 0	UNITS CONTAINED PACKAGING 1	PACKAGING VOLUME UNIT MMQ
UNITARY PACKAGING LENGTH 0	PACKAGING HEIGHT 365	PACKAGING GROSS WEIGHT 0
UNITARY PACKAGING VOLUME 0	PACKAGING WIDTH 192	PACKAGING NET WEIGHT 1.95
UNITARY PACKAGING GROSS WEIGHT 1.95	PACKAGING LENGTH 95	PACKAGING WEIGHT UNIT KGM
PRODUCT NET WEIGHT 1.95		