

Extension 1.5 metres for aluminium column with 2 sides oval Simon K45

REF. ALK72P15/8



BASIC INFORMATION

DESCRIPTION

Among Simon's fixed to the floor products, is this extension of 1.5 metres aluminium oval column with two sides. It is part of the series Simon K45. It can withstand extreme temperatures, ranging from -25 degrees centigrade up to the + 120 degrees centigrade maximum. With measures of 1500 x 80 millimetres and a depth of 110 millimetres in total, this extension for column a stylish metallic finish. To accomplish this, anodised aluminium was used in its manufacture. To ensure the robustness of the set, it is only possible to combine one extension per column. For its correct maintenance, simply use a very soft cloth, cotton, and completely dry cloth for cleaning. Always avoid the use of aggressive chemical products, with the manufacturing materials of this extension. Simon guarantees the security of all its products fixed to the floor, as well as the best functionality of the same.

FINISH

Metal

COMPATIBILITY

Simon K45 functions

ETIM CLASS

EC000795

MATERIAL

Aluminium

PACKAGING CONTENTS

Column extension, front cover, connecting pins and screws

REMARKS

To ensure the robustness of the unit, it is only possible to combine one extension per column.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

2-sided (square and oval) and 4-sided

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120° C

EARTHING RESISTANCE

< 0.05 ?

ELECTRICAL PROPERTIES

With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Separation by means of the compartments of the extension itself to eliminate any possible electromagnetic interference and transmission errors between the electric cables and Voice, Data and Multimedia.

HEAT RESISTANCE (°C)

+650°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)

5 MOhms at 500 V.

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 a 120° C

VERSION

2-sided (Oval)

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

TYPE OF FASTENING

Using connecting pins

REMOVAL OF COVER

Only with tool

INSTALLATION DIRECTION

Vertical

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436050563

PRODUCT NET WEIGHT

4

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

31834880

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436050563

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

31834880

PACKAGING HEIGHT

88

PACKAGING NET WEIGHT

4

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

119

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

4

PACKAGING LENGTH

3040