

## Customisable kit with dual opening cover and brushes, 6 schuko socket outlets and 2 empty elements white S400 Indesk Duo

REF. 46403000-130



## BASIC INFORMATION

### DESCRIPTION

With a cover for 2 opening and brushes we find this kit within the table customizable for 6 SCHUKOS and 2 empty elements in white finish of the series Simon 400 Indesk Duo. It has a connector figure Wieland ® gst18i 3 poles male in-line with patch cord of 22 centímetros, a insulation resistance > 5 M $\Omega$  at 500 V and is made for 6 sockets for standard current circuit of 250 volts and 16 amps. A piece created for last for since it has an enclosure do painted and a profile in anodised aluminium. Also, is designed for that no flame spread or be created fumes toxic in case of fire, since its covers and fastenings are manufactured in self-extinguishing thermoplastic and halogen-free. To complete the installation of this product, we must use the functions of the series Simon 400 Indesk Duo.

### FINISH

White

### MATERIAL

Metal

### COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

### PACKAGING CONTENTS

Pre-wired profiles, enclosure, fastening claws, 3-pole T-branching with 1 male input and 2 female outputs and installation manual.

### ETIM CLASS

EC002759

### REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with brush

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

### NUMBER OF POSSIBLE ELEMENTS

2

### FORMAT

Schuko

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### IK CLASSIFICATION

07

### INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

### CURRENT (A)

16 A

### IP RATING

IP30

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

### NOMINAL VOLTAGE (V~)

250 V~

### OPERATING TEMPERATURE RANGE (°C)

-5...+60

### TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL

9016

### NUMBER OF REAR ENTRANCES

2

### RECESS DIMENSION (MM)

228 x 175 mm (± 2mm)

### NUMBER OF SOCKETS

6 sockets for standard current circuit

### VERSION

8 elements

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS

With brush

### CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

### REMOVAL OF COMPONENTS

### NUMBER OF COVER OPENING POSITIONS

2

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING

By lateral tightening of claws provided with the enclosure.

Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

### REMOVAL OF THE FRAME

Only with tool

### INSTALLATION TYPE

Suitable for recessed mount in furniture.

### OPENING ORIENTATION

At 45° and 135°

### REMOVAL OF THE PLATE

Only with tool

### SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD; Directiva 2011/65/UE RoHS; EN 50581:2012; EN 60670-1:2005; EN 60670-1:2005 A1:2013; IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053197028

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

2.35

### PRODUCT NET WEIGHT

2.35

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053197028

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

370

### PACKAGING WIDTH

135

### PACKAGING LENGTH

200

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

9990000

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

2.35

### PACKAGING WEIGHT UNIT

KGM