

LedFlex 810.52 4000 K IP20 5 mm

REF. 81052000-984



BASIC INFORMATION

APPLICATION

General lighting, Indoor decorative lighting

PACKAGING CONTENTS

1 unit (5m)

ETIM CLASS

EC002706

TECHNICAL INFORMATION

IP RATING

IP20

DRIVER INCLUDED

No

LUMENS (LM)

6800 lm

OPERATING TEMPERATURE RANGE (°C)

-20 - 40 °C

L70 (°C)

30,000 h

LUMENS/W

6800 lm/72W

COLOR TEMPERATURE (K)

4000 K

LIGHT BEAM APERTURE ANGLE (°)

120°

OPTICS

General

CONTROL

PWM

COLOR TYPE

NW

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CRI

80

LIGHTING EFFICIENCY (LM/W)

94,4 lm/W

POWER (W)

72 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Hardware

REGULATIONS

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY EAN CODE 8421053203088	UNITARY PACKAGING WEIGHT UNIT KGM	PACKAGING MEASUREMENT UNIT MMT
UNITARY PACKAGING HEIGHT 0	PACKAGING EAN 8421053203088	PACKAGING VOLUME 1200
UNITARY PACKAGING WIDTH 0	UNITS CONTAINED PACKAGING 1	PACKAGING VOLUME UNIT MMQ
UNITARY PACKAGING LENGTH 0	PACKAGING HEIGHT 2	PACKAGING GROSS WEIGHT 140.2
UNITARY PACKAGING VOLUME 0	PACKAGING WIDTH 24	PACKAGING NET WEIGHT 0.14
UNITARY PACKAGING GROSS WEIGHT 0.14	PACKAGING LENGTH 25	PACKAGING WEIGHT UNIT GRM
PRODUCT NET WEIGHT 0.14		