

Luminaire P1 9,4W 3000K with detector 8m HF+LUX IP54

REF. 89194000-093



BASIC INFORMATION

DESCRIPTION

Luminaire with integrated HF detector, power 9.4 W, luminous flux of 940 lm, and color temperature 3000 K. The maximum installation height is 4m and the installation is surface-mounted. The detection range is 8m and the detection angle is 360°. The brightness regulation range is 2 - 2000 lux and the timing range is 5 s - 15 min. It allows interconnection of master/master and master/slave luminaires. The power supply voltage is 220 - 240 VAC. The operating temperature is: -10 - 40 °C. Protection rating IP 54 and IK 3 with dimensions: Ø 280 x 110 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

IK CLASSIFICATION

03

MAXIMUM POWER (W)

400

CONTROL

On/Off

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053370698

UNITARY PACKAGING GROSS WEIGHT

0.73

PACKAGING LENGTH

300

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.386

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2325323

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053370698

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.73

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

300

PACKAGING NET WEIGHT

0.386

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

120

PACKAGING WEIGHT UNIT

KGM