

Downlight 800.22 White 24W 3000K DALI2

REF. 80022330-683



BASIC INFORMATION

APPLICATION

General technical lighting

PACKAGING CONTENTS

1 Units

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

80

LUMENS/W

2400 lm/24W

IP RATING

IP54

ELECTRICAL CLASS

tipo 2

OPTICS

Extensive

OPERATING TEMPERATURE RANGE (°C)

-15°C a 35°C

L70 (°C)

50.000 h a 25°C

PHOTOBIOLOGICAL CLASSIFICATION

Categoría exento

POWER SUPPLY (V~)

220/240 V~

LIGHT BEAM APERTURE ANGLE (°)

60°

POWER (W)

24W

COLOR TEMPERATURE (K)

4000K

COLOR TYPE

NW

SERVICE LIFE

50.000 h

CONTROL

DALI2

LIGHTING EFFICIENCY (LM/W)

105 lm/W

COS Φ

0.95

LUMENS (LM)

2400 lm

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

115

INSTALLATION TYPE

Recessed

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50.000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053304471

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.678

PRODUCT NET WEIGHT

0.678

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053304471

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

135

PACKAGING WIDTH

195

PACKAGING LENGTH

230

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

6054750

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.868

PACKAGING NET WEIGHT

0.678

PACKAGING WEIGHT UNIT

KGM