

Modular luminaire 720 Advance M4 60x60 Low Glare NW

REF. 72060040-684



BASIC INFORMATION

DESCRIPTION

Reduce by up to 20% of the energy consumption of its luminaire with the range of modular luminaires 720 of Simon. With micro prismatic optics and a light of a white neutral, with a temperature of 4000 K NW, the luminaire modular Advance M4 60x60, it is the ideal option to promote energy savings, maximizing the quality and functionality of its lighting system. With a luminous light flux 3400 lm / 28W, their service life is 100,000 hours for the L70 at 25 ° C and 40,000 hours for the L90. Also, this luminaire is compatible with a voltage of power 100... 240 Volt and 50-60 Hertz rate. With control of switching on ON-OFF, it is designed for installation in false ceiling, visible hardware in both surface-mounted and flush mounted. The versatility of installation linked to its size of 595 x 595 mm and with a few finishes in white, guaranteeing the integration of the set in the space, providing a current and minimalist style.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

121 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Tipo 2

LUMENS (LM)

3400 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

3400 lm/28W

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Microprismatic

COLOR TEMPERATURE (K)

4000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

CONTROL

On/Off

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

28 W

CRI

82

COLOR TYPE

NW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

INSTALLATION TYPE

False ceiling, visible hardware

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053191705

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053191705

PACKAGING VOLUME

23400000

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

65

PACKAGING GROSS WEIGHT

5.76

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

600

PACKAGING NET WEIGHT

5

UNITARY PACKAGING GROSS
WEIGHT

5.76

PACKAGING LENGTH

600

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

5