

Configured Teleblock telescopic profile with manual elevation aluminium Simon K45

REF. KTL222



BASIC INFORMATION

DESCRIPTION

The Teleblock telescopic profile with manual elevation configured of the series Simon K45 has fast-terminals connection and 2 modules in a piece of furniture with black finishes in. This is a solution which profile is made in anodised aluminium, whose brackets for fastening and top closure and bottom you are in self-extinguishing thermoplastic and halogen-free. In this way, it guarantees no flame spread in case of fire having fire and a minimum toxicity in the event of smoke generation. This profile measures 103x60x242 mm, it is suitable for flush mounting in furniture and is compatible with elements up to 16 A of intensity and 250 V of voltage. To complete the installation of the product, it must be combined with the cover and trim frame whose references are KTLA1 / 14 or KTLA1 / 31.

FINISH

Black

MATERIAL

Metal

ETIM CLASS

EC002759

REMARKS

To complete the installation of the product it must be combined with the cover and trim frame (refs. KTLA1/14 or KTLA1/31).

TECHNICAL INFORMATION

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the silicone gasket on the cover that prevents the entry of external elements when there are no connections.

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Ensured by the fixing of the metal separator in the rail enabled in the bracket for this purpose.

FORMAT

French

INDICATOR FUNCTION

No

CURRENT (A)

16 A

IP RATING

IP4X

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

NUMBER OF MODULES

2

MONOBLOCK

No

RAL

7021

RECESS DIMENSION (MM)

Ø 114 mm

VERSION

2 elements

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

REMOVAL OF COMPONENTS

Only with tool

NUMBER OF COVER OPENING POSITIONS

1

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+850 °C (according to standard IEC 60670)

TYPE OF FASTENING

By tightening the fastening thread supplied with the Simon K45 Teleblock telescopic profile.

INSTALLATION DIRECTION

Horizontal, Vertical

REMOVAL OF THE PLATE

Only with tool

SECURING POSSIBILITIES

Its design allows integration in any type of furniture, combining the telescopic profile with the cover and decorative frame (ref. KTLA1/14 black finish, ref. KTLA1/31 matte chrome finish)

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

MOUNTING WITHOUT ACCESSORIES

The telescopic profile is supplied with all necessary installation materials, including the fastening bracket, without needing additional references for attachment.

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436063877

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8426436063877

PACKAGING VOLUME

13.332

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

140

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

214

PACKAGING NET WEIGHT

1.396

UNITARY PACKAGING GROSS
WEIGHT

1.396

PACKAGING LENGTH

445

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

1.396