

Aluminium bracket Ofiblock Line for 2 elements with 2 access points for rear wiring graphite Simon K45

REF. KFC132/14



BASIC INFORMATION

DESCRIPTION

Ofiblock Line aluminium profile of two elements and two modules. It has 2 accesses for rear cabling. The finish of this profile is a current graphite grey colour and is part of the series Simon K45. The exact dimensions of the profile are 54 x 136 millimetres and a depth of 54 millimetres. The profile includes a blind plate that permute the most comfortable distribution of cabling by its indoor. It is not monoblock and withstands temperatures of up to + 60 degrees centigrade. It is as resistant to heat by its manufacturing materials. It is created in anodised aluminium and side covers in self-extinguishing thermoplastic components and halogen-free. This guarantees the security as to prevent the propagation of the flame in case of fire. This profile account, in addition, with two inputs of cabling later, which allows the best solutions for the convergence of energy, voice, data and multimedia solutions in any type of furniture.

FINISH

Graphite

MATERIAL

Metal

COMPATIBILITY

Simon K45 range functions and possible to combine with the Simon Electrical Wiring range.

PACKAGING CONTENTS

Ofiblock Line aluminium bracket with rear accesses, 1 ground connection, 1 blind plate, 2 caps to cover rear accesses, 2 side blind covers, screws and installation manual.

REMARKS

Has 2 rear cable inlets for the convergence of energy, voice and data and multimedia solutions in any furniture.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP4X

NUMBER OF MODULES

2 modules

AVAILABLE IN

Available in 1, 2, 4 and 6 elements.

KIT AVAILABILITY

Yes

RAL

7021

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

LINKABLE

No

NUMBER OF REAR ENTRANCES

2

HEAT RESISTANCE (°C)

+125°C (according to standard IEC 60670)

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SPACE FOR CABLING DISTRIBUTION

The bracket is supplied with 1 blind plate for easier internal wiring distribution.

INSULATION RESISTANCE (V-MΩ)

>5 MOhm at 500 V

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

2 elements

INSTALLATION AND MAINTENANCE

CABLING ACCESS

Through the housings on the sides and rear section of the bracket.. Input for electrical wiring lead and voice/data or multimedia wiring.. Possibility of supply with machining on the side covers according to customer needs (upon request).

EXTINGUISHING (°C)

+850 °C (according to standard IEC 60670)

REMOVAL OF THE PLATE

Only with tool

REMOVAL OF COMPONENTS

Only with tool

INSTALLATION DIRECTION

Horizontal.

MOUNTING WITHOUT ACCESSORIES

The profile is attached to the Ofiblock Line frame by folding the 4 fixing tabs, without needing accessories.

REMOVAL OF COVER

Only with tool

INSTALLATION TYPE

Suitable for embedding in furniture.

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053117828

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.175

PRODUCT NET WEIGHT

0.175

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053117828

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

59.5

PACKAGING WIDTH

183

PACKAGING LENGTH

54.5

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1275000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.175

PACKAGING WEIGHT UNIT

KGM