

Complete set with 6 schuko socket outlets white S400 Top

REF. 42606000-130



BASIC INFORMATION

DESCRIPTION

Desk top kit, of the series Simon 400 Top, white in colour and has 6 socket-outlets socket. It has dimensions of 295 x 120 x 80 mm and has a current of 16 A and works with a voltage of 250V. It is manual elevation and access to the cabling is done with brush strip. It is made in the following materials: The trim cover in painted steel, the profile in anodised aluminium and the covers and fastenings in self-extinguishing thermoplastic and halogen-free that promotes the no flame spread in case of fire (in case of fire) and a low level of toxicity (in the event of smoke generation). Its cleaning is very easy to perform as it will only need to wipe it with a soft and dry cloth and never use abrasive cloths or cleaners containing chlorine in its formulation, as it could be damaged and does not offer their functions at full.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

NOMINAL VOLTAGE (V~)

250 V~

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

CURRENT (A)

16 A

TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

IP RATING

IP30

RAL

9016

FORMAT

Schuko

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

NUMBER OF SOCKETS

6 sockets for standard current circuit

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

VERSION

6 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

SECURING POSSIBILITIES

Using clips included in the fastening brackets

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

INSTALLATION TYPE

Suitable for fixing to furniture.

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053196182

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.15

PRODUCT NET WEIGHT

1.15

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053196182

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

330

PACKAGING WIDTH

125

PACKAGING LENGTH

95

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3918750

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.15

PACKAGING WEIGHT UNIT

KGM