

Wall solar luminaire SOL-O S 3,3W 3000K with detector 6m PIR+LUX anthracite IP44 3Y

REF. 89198002-033



BASIC INFORMATION

DESCRIPTION

Solar wall light with PIR sensor. The power is 3.3 W, the luminous flux is 273 lm, and the color temperature is 3000 K.

The maximum installation height is 3 m, and the installation is on the wall (surface). The detection range is 6 m, and the detection angle is 360 °.

The luminosity regulation range is 2 - 2000 lux, and the timing range is 10 s - 30 s.

The luminaire configuration is done through potentiometers.

It is powered by solar energy. The operating temperature is: -20 - 40 °C.

Protection rating IP 44 and IK 03 and dimensions: 240 x 90 x 53 mm.

3-year warranty.

For more product information, visit the STEINEL website by clicking [here](#).

FINISH

Anthracite

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP44

POWER SUPPLY (V~)

220/240 V~

IK CLASSIFICATION

03

OPERATING TEMPERATURE RANGE (°C)

-20...+40

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Wall surface mounting

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053442890

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.845

PRODUCT NET WEIGHT

0.557

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053442890

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

260

PACKAGING WIDTH

125

PACKAGING LENGTH

125

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.845

PACKAGING NET WEIGHT

0.557

PACKAGING WEIGHT UNIT

KGM