

Surface mount thermostat for cooling or heating graphite Simon 75

REF. 75503-68



BASIC INFORMATION

DESCRIPTION

The temperature in a room has a direct impact on the actions carried out in it. Having the temperature control that best suits each situation will allow us to carry out our objectives in the best environmental conditions, as bad is an excess of heat in winter and too cold in summer. With the graphite surface-mounted thermostat for heating or cooling of the Simon 75 series you can always create the ambience you want to have in each circumstance. It is a device with screw-terminal connection and a type of rotary operation and pulsation analogue with a temperature range of 5 to 30 °. The metal components with halogen-free thermoplastic insulation of its materials make it a thermostat that is highly resistant to wear and tear and the passage of time, it is essential to the power of the resistance for proper operation and has an ON-OFF switch.

FINISH

Graphite

PACKAGING CONTENTS

Surface-mounted thermostat
and instruction sheet

ETIM CLASS

EC010927

REMARKS

It is essential to supply power to the resistor so that it operates properly.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

FREQUENCY

50 Hz

RELAY OUTPUT CURRENT (A)

10 (4 Inductive) A

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

STORAGE TEMPERATURE RANGE

(°C)

-20 - 75 °C

AIR CONDITIONING CONTROL

Yes

TYPE OF MECHANISM

Rotary and press

TYPE

Heating system

NUMBER OF CONTACTS

7

OPERATING TEMPERATURE

RANGE (°C)

0 - 40 °C

VERSION

Single

NUMBER OF CONTROLLABLE CIRCUITS

1

MODE OF OPERATION

Analogue

ENTRY FOR WINDOW CONTACT

No

NUMBER OF POSSIBLE ELEMENTS

1

POWER SUPPLY (V~)

230 V~

NUMBER OF WIRES

6

INSTALLATION AND MAINTENANCE

CLAW

Not possible

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Screw

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2011/65/UE RoHS + post. mod. | EN 60730-2-9:2010 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053028995

PRODUCT NET WEIGHT

0.11

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

267325

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053028995

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.11

UNITARY PACKAGING VOLUME

267325

PACKAGING HEIGHT

85

PACKAGING NET WEIGHT

0.11

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

37

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.11

PACKAGING LENGTH

85