


Rocker for single-pole switching mechanisms for 1 element aluminium Simon K45

REF. K110/8



BASIC INFORMATION

DESCRIPTION

With the simplicity and elegance of a few finishes, the aluminium rocker for single-pole switching mechanisms of the collection Simon 45, coupled functionality, appearance and innovation in a reduced space, perfect for offices and working areas. Engineered for 1 element, is composed with halogen-free thermoplastic materials that guarantee the security of the room in case of fire, to prevent the flame spread and toxicity by smoke. Thanks to this material can exceed temperatures of more than 60 °C. With a size of 45 x 45 mm and a depth of 10 mm, it is suitable for installation both recessed and surface-mounted, adapting to the needs of each space aesthetic and functional.

FINISH

Aluminium

MATERIAL

Plastic

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

Rocker and installation manual

ETIM CLASS

EC000011

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

AVAILABLE IN

Quarter and half module versions

KIT AVAILABILITY

No

NUMBER OF MODULES

Half

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INDICATOR FUNCTION

No

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-033)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

TYPE OF FASTENING

Fixing by direct snap-fit, no tools needed

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-1:1999 + EN 60669-1:1999 A1:2002 + EN 60669-1:1999 A2:2008

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
544320

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
0.012

PRODUCT NET WEIGHT
0.012

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8426436047051

UNITS CONTAINED PACKAGING
5

PACKAGING HEIGHT
72

PACKAGING WIDTH
72

PACKAGING LENGTH
105

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
544320

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.06

PACKAGING NET WEIGHT
0.06

PACKAGING WEIGHT UNIT
KGM