

Extension 0.5 metres for aluminium column with 1 side white Simon 500 Cima

REF. 53555101-030



BASIC INFORMATION

DESCRIPTION

This product is the ideal complement for columns of one side of the Simon 500 Cima series, since it is a 0.5 metre extension for this type of column. The extension is suitable for installing on any floor type, whether concrete or raised and can also be set the pole using a telescopic guide attached to the ceiling slab. It is therefore a highly versatile product and multifunctional, as it offers multiple possibilities of use. It has dimensions of 500 x 110 millimetres and 72 millimetres of depth and only to be taken into account is that to ensure the robustness of the total structure, it is advisable to combine only one extension per column. The product is presented in a classic colour white that make it ideal for any type of room where it is, as it integrates with ease regardless of the predominant appearance. The column is made of high quality aluminium, so that it is a very resistant product of great hardness, which extends its service life.

FINISH

White

MATERIAL

Aluminium

COMPATIBILITY

Simon 500 Cima, Simon 27 Play/Simon K45 (using adaptor) mechanisms and universal Simon mechanisms in combination with the universal box designed specifically for columns.

PACKAGING CONTENTS

Extension and installation manual

ETIM CLASS

EC000795

REMARKS

To ensure the robustness of the total structure, it is only possible to combine one extension per column

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

1 and 2 sides

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120 °C

EARTHING RESISTANCE

< 0.05 Ohms

ELECTRICAL PROPERTIES

With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured with the metal divider
guide supplied in the column.

IP RATING

IP4X

MAINTENANCE

Clean with a soft, dry cloth. Do
not use abrasive cloths or
cleaning products that contain
chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 to +120 °C

RAL

9003

VERSION

1 side

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Using connecting pins

INSTALLATION DIRECTION

Vertical, corresponding with the
direction of the mechanisms

INSTALLATION TYPE

Suitable for installing in any floor
type, raised or concrete. Column
secured by applying pressure to
the ceiling slab using a
telescopic guide.

REMOVAL OF TRIM FRAMES

Only with tool

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053101827

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053101827

PACKAGING VOLUME

31.835

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

88

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

119

PACKAGING NET WEIGHT

1.35

UNITARY PACKAGING GROSS
WEIGHT

1.35

PACKAGING LENGTH

3040

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

1.35