Module for 1 Keystone II RJ45 AMP®, Brand Rex® or Simon® in angled voice and data plates

REF. **MD67**



BASIC INFORMATION

DESCRIPTION

This product consists of a module for 1 Keystone II RJ45 from AMP ®, Brand Rex ® or Simon ® in angled voice and data belonging to the Simon 500 Cima series. The module is exclusively designed for plates of this range of type inclined, as the angled voice and data plates for Simon are included with the module. Its dimensions are 32 x 20 millimetres and 10 millimetres of depth, and its installation is very simple. The product is made of thermoplastic insulation. These components are of the highest quality, as well as all the used by Simon. Thanks to the product has a resistance and hardness extra that extends considerably its service life and allows you to operate even low temperatures ranging from -5 and 60 degrees centigrade. Added to all this is the capacity of the module extinguish the spread in case of fire management and reduces the toxicity in the flue gas in case of producing. Which contributes without a doubt to increase in a considerable the security of the end product.

COMPATIBILITY

Simon 500 Cima and Simon K45 angled voice and data plates

PACKAGING CONTENTS

MD Module for 1 RJ45

ETIM CLASS

EC002948

REMARKS

The MD Module can only be combined with angled voice and data plates (flat voice and data plates include the MD Module on the plate itself).

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

COMPATIBLE WITH CONNECTORS
Simon®, AMP netconnect® Series Standard 110, SL110, SL Tool less, Brand-Rex®, Panduit® Series Netkey, Rit® and manufacturers of RJ45 with Keystone II snap-fit system.

RJ45 CONNECTORS
Not included in the MD Module

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60 °C

FORMAT
RJ45

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60 °C

SNAP-FIT RJ45 PLATES
RJ45 AMP®, Brand Rex® or Simon® connectors

SNAP-FIT TYPE
RJ45 AMP®, Brand Rex® or Simon® connectors

INSTALLATION AND MAINTENANCE

INSTALLATION DIRECTION
Vertical, corresponding with the MD Module fastening slots

INSTALLATION TYPE
Fixing by direct snap-fit, no tools needed.

REGULATIONS

REGULATIONS
Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.003

PRODUCT NET WEIGHT
0.003

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436025394

UNITS CONTAINED PACKAGING
50

PACKAGING HEIGHT
65

PACKAGING WIDTH
70

PACKAGING LENGTH
100

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
455000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.15

PACKAGING NET WEIGHT
0.15

PACKAGING WEIGHT UNIT
KGM