Adjustable depth drawer for 6 S modules to be installed in a false floor color graphite Simon CIMA

REF. **SF610/14**



BASIC INFORMATION

FINISH

Graphite

MATERIAL

Various

COMPATIBILITY

With Simon Series S mechanisms and Simon 25 / Simon K45 (via adapter)

ETIM CLASS

EC000024

TECHNICAL INFORMATION

NUMBER OF CLAMP-HOLDER HOLES
16

HEAT RESISTANCE (°C)
+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION
08

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)
1800kg

RAL
7021

RECESS DIMENSION (MM)
210 x 300 mm

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

NUMBER OF COVER OPENING POSITIONS
2

REMOVAL OF COVER
Only with tool

EXTINGUISHING (°C)
+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

REMOVAL OF THE FRAME
Only with tool

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436052628

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
2.248

PRODUCT NET WEIGHT
2.248

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436052628

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
98

PACKAGING WIDTH
230

PACKAGING LENGTH
332

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
7483280

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
2.27

PACKAGING NET WEIGHT
2.248

PACKAGING WEIGHT UNIT
KGM