

## Complete kit with cover, brush, 2xUSB cover and 3 schuko socket outlets black S400 Indesk

REF. 44423000-138



### BASIC INFORMATION

#### DESCRIPTION

A charger 2 x USB and three schuko socket bases for standard current circuit make up the kit integrated into the table complete with cover and brush in black color from the Simon 400 Indesk series. Suitable for flush mounting in furniture, it has a current of 16 A and a voltage of 250 V~, as well as a Wieland® gst18i connector with three male poles aerial with a patch cord of 22 cm. It also has an insulation resistance of >5 MO at 500 V and a dielectric strength without puncture or contouring with 2000 V at 50 Hz for one minute. This kit stands out for its resistance and durability over time thanks to the components it has been designed with: painted steel enclosure, anodized aluminum profile, covers, and fittings in self-extinguishing thermoplastic and halogen-free that prevent flames and gases in case of fire.

#### FINISH

Black

#### MATERIAL

Metal

#### COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

#### PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

#### ETIM CLASS

EC002759

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with brush

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

### FORMAT

Schuko

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### IK CLASSIFICATION

07

### INSULATION RESISTANCE (V-MΩ)

>5 MΩ a 500 V

### CURRENT (A)

16 A

### IP RATING

IP30

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

### NOMINAL VOLTAGE (V~)

250 V~

### OPERATING TEMPERATURE RANGE (°C)

-5...+60

### TYPE OF POWER SUPPLY CONNECTOR

Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL

9005

### RECESS DIMENSION (MM)

228 x 175 mm (± 2mm)

### NUMBER OF SOCKETS

3 sockets for standard current circuit

### NUMBER OF USB CHARGERS

1

### VERSION

5 elements

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS

With brush

### CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

### NUMBER OF COVER OPENING POSITIONS

1

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

### REMOVAL OF THE FRAME

Only with tool

### INSTALLATION TYPE

Suitable for recessed mount in furniture.

### OPENING ORIENTATION

At 45°

### SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053219263

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

1.85

### PRODUCT NET WEIGHT

1.85

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053219263

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

90

### PACKAGING WIDTH

195

### PACKAGING LENGTH

275

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

4826250

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

1.85

### PACKAGING WEIGHT UNIT

KGM