

Double schuko socket 16 A 250V~ with safety device, light indicator and screw terminal connection graphite Simon Cima

REF. S1/14



BASIC INFORMATION

FINISH

Graphite

COMPATIBILITY

With all the enclosures of the Simon Cima range.

ETIM CLASS

EC000125

TECHNICAL INFORMATION

FORMAT

Schuko

HEAT RESISTANCE (°C)

+125 °C (in accordance with standard IEC 60695-10-2)

INDICATOR FUNCTION

Yes

CURRENT (A)

16 A

IP RATING

IP20

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MONOBLOCK

No

RAL

7021

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

INSTALLATION DIRECTION

Horizontal, Vertical

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.112

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

3769392

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436021075

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

1.12

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

118

PACKAGING NET WEIGHT

1.12

UNITARY PACKAGING GROSS
WEIGHT

0.112

PACKAGING WIDTH

121

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

264