

Modular luminaire Clean room 60x60 4000K

REF. 75501330-394



BASIC INFORMATION

DESCRIPTION

Sealed LED luminaire 755 (595x595mm) with multilayer front (microprismatic diffuser + tempered glass) for demanding environments. CRI90, 4000K, UGR<19. DALI-2 driver with energy report and diagnostics. IP65, IK08. Power 45W, output 4900lm, efficiency 109 lm/W. Perfect for hospitals, labs, clean rooms. Complies with UNE EN ISO 14644 Class 1.

FINISH

White

APPLICATION

Healthcare

MATERIAL

Aluminium

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

NOMINAL VOLTAGE (V~)

220/240 V~

CONTROL

DALI2

IK CLASSIFICATION

08

OPERATING TEMPERATURE

RANGE (°C)

-20...+35

COLOR TYPE

NW

IP RATING

IP65

POWER SUPPLY (V~)

220/240 V~

OPTICS

Diffused

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053360064

UNITARY PACKAGING GROSS WEIGHT

9.2

PACKAGING LENGTH

600

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

8.6

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

39600000

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053360064

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

9.5

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

110

PACKAGING NET WEIGHT

8.6

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

600

PACKAGING WEIGHT UNIT

KGM