

German socket outlet 16A 250V~ with hinged cover, safety device and screw terminal connection ivory Simon 27 Play

REF. 27490-32



BASIC INFORMATION

DESCRIPTION

Schuko socket outlet with an intensity of 16 A and a voltage of 250V. It has a safety device and screw terminal connection. Its ivory finish and is part of the Simon 27 Play series. Its type of operation is by insertion and socket is a perfect to be recessed and for installation in surface-mounted. It is fully compatible with the frames Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralizations and Simon 44 Aqua and the covers include child protection function. It measures 45x45mm and is manufactured in accordance with the regulations IEC 60884-1 ED 3.2 + UNE 20315-1-1: 2009 + UNE 20315-1-2: 2009 standard and with metal components with halogen-free insulation and thermoplastic trim. If you want to clean this socket outlet, just use a soft, dry cloth and not to use never or abrasive cleaners or cloths that contain chlorine in its formula.

FINISH

Ivory

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Socket outlet with hinged cover

ETIM CLASS

EC000125

REMARKS

The covers include a child-proof protective feature.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

16 A

MONOBLOCK

No

CABLE SECTION ADMITTED (MM)

2,5 mm

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

FORMAT

Schuko

TYPE OF MECHANISM

Insertion

VERSION

Single

INDICATOR FUNCTION

No

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

15

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American and Centralisations

INSTALLATION TYPE

Suitable for surface and flush mounting

CLAW

Simon 27

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | UNE 20315-1-1:2017 | IEC 60884-1 Ed 3.2 | UNE 20315-1-2:2017

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053252338

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

1531530

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.054

PRODUCT NET WEIGHT

0.054

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053064979

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

55

PACKAGING WIDTH

91

PACKAGING LENGTH

306

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1201200

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.54

PACKAGING NET WEIGHT

0.54

PACKAGING WEIGHT UNIT

KGM