

German socket outlet monoblock IP55 16A 250V~ with safety device and fast terminal connection grey Simon 44 Aqua

REF. 4490432-035



BASIC INFORMATION

DESCRIPTION

Schuko monoblock socket-outlet with, IP55, 16A current and a voltage of 250V. It, in addition, with safety device, it belongs to the series Simon 44 Aqua and is finished in grey colour. Its clamping is fast type and its operation is by insertion. With 1 element and supports a section of wire 2.5 mm with a stripped 15 mm and can be position, place in rooms with a temperature located between 5 and 40°C, approximately, although it is able to withstand extreme temperatures of -25 to 50°C, plus or minus. It is made of metal components with halogen-free insulation and thermoplastic trim, materials that are very easy to clean because it will only need to use a soft and dry cloth and never use abrasive cloths or cleaners containing chlorine. Its dimensions are 84x75 mm and has a depth of 57,5 mm

FINISH

Grey

PACKAGING CONTENTS

Socket outlet, base and frame with cover

ETIM CLASS

EC000125

COMPATIBILITY

Simon 27 mechanisms

TECHNICAL INFORMATION

AVAILABLE MARKET CE	CURRENT (A) 16 A	NOMINAL VOLTAGE (V~) 250 V~
CABLE SECTION ADMITTED (MM) 2,5 mm	IP RATING IP55	OPERATING TEMPERATURE RANGE (°C) 5 - 40 °C
NUMBER OF POSSIBLE ELEMENTS 1 element	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	RAL 7035
FORMAT Schuko	TYPE OF MECHANISM Insertion	STORAGE TEMPERATURE RANGE (°C) -25 - 50 °C
IK CLASSIFICATION 07	MONOBLOCK	VERSION Single
INDICATOR FUNCTION No		

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 15	INSTALLATION DIRECTION Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Fast
	INSTALLATION TYPE Suitable for surface mounting	

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018*1 | IEC 60884-1 Ed. 3.2*2 | UNE 20315-1-1:2017*2 | UNE 20315-1-2:2017*2 | EN IEC 60670-1:2021 + A11:2021*3 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053069905

PACKAGING VOLUME
4.079

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
10

PACKAGING VOLUME UNIT
DMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
86

PACKAGING GROSS WEIGHT
1.75

UNITARY PACKAGING GROSS
WEIGHT
0.168

PACKAGING WIDTH
155

PACKAGING NET WEIGHT
1.68

PRODUCT NET WEIGHT
0.168

PACKAGING LENGTH
306

PACKAGING WEIGHT UNIT
KGM