

Downlight 725.27 3000K 1-10V

REF. 72527130-883



BASIC INFORMATION

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

80

LUMENS/W

1400 lm/14 W

IP RATING

IP44

ELECTRICAL CLASS

Type 2

OPTICS

General

OPERATING TEMPERATURE RANGE (°C)

-10 - 35 °C

L70 (°C)

54.000 h at 25°C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

POWER SUPPLY (V~)

220/240 V~

LIGHT BEAM APERTURE ANGLE (°)

112°

POWER (W)

14 W

COLOR TEMPERATURE (K)

3000 K

LIGHTING EFFICIENCY (LM/W)

100 lm/W

SERVICE LIFE

50.000 h

CONTROL

1-10 V

LUMENS (LM)

1400 lm

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Flush mount

REGULATIONS

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053282434

UNITARY PACKAGING HEIGHT

55

UNITARY PACKAGING WIDTH

18

UNITARY PACKAGING LENGTH

22

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

21780

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.56

PRODUCT NET WEIGHT

0.328

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053282434

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

55

PACKAGING WIDTH

18

PACKAGING LENGTH

22

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

21780

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.56

PACKAGING NET WEIGHT

0.328

PACKAGING WEIGHT UNIT

KGM