

MD-20 180° PIR+LUX SR wall surface DALI-2 Master white IP54

REF. 89202435-230



BASIC INFORMATION

DESCRIPTION

Surface PIR motion and light detector. The recommended installation height is 2.5 m, with a maximum height of 2.5 m. It has a detection angle of 180° and an opening angle of 90°. The tangential detection range is 20 m and the radial detection range is 4 m.

The luminosity regulation range is 2 - 1000 lux and the timing range is 5 s - 15 min. The detector configuration is done through potentiometers and remote control.

It features TEACH operating mode. Possibility of interconnection between sensors through DALI. The control protocol is DALI-2 Master. The number of dimmable luminaires through the DALI bus is 30 (1 group).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C.

White finish, IP 54 protection degree and dimensions: 95 x 95 x 65 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

CONTROL

DALI2 Master

IP RATING

IP54

RAL

9003

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

1.8

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053380741

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.253

PRODUCT NET WEIGHT

0.164

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053380741

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

90

PACKAGING WIDTH

124

PACKAGING LENGTH

160

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.253

PACKAGING NET WEIGHT

0.164

PACKAGING WEIGHT UNIT

KGM