

Double element access cover for installation on pavement or technical floor graphite Simon Cima

REF. S100/14



BASIC INFORMATION

FINISH

Graphite

MATERIAL

Various

COMPATIBILITY

With plastic buckets of 1 double element Simon Cima when installed on floor pavement.

ETIM CLASS

EC001903

TECHNICAL INFORMATION

HEAT RESISTANCE (°C)

+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION

08

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL

7021

RECESS DIMENSION (MM)

170 x 115 mm

INSTALLATION AND MAINTENANCE

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

CAN BE INSTALLED IN TRAY

Plástica

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436020085

PRODUCT NET WEIGHT

0.55

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2871375

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436020085

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.55

UNITARY PACKAGING VOLUME

2871375

PACKAGING HEIGHT

95

PACKAGING NET WEIGHT

0.55

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

155

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.55

PACKAGING LENGTH

195