Mini jack connector female with trim plate white Simon K45

REF. **K123B/9**



BASIC INFORMATION

DESCRIPTION

Provides the maximum workplace solutions to its devices for audio and other systems with the analog mini jack connector 2.5 mm of Simon K45. This connector has a trim cover in white tone that, with its finishes simple, gives your room, the greater functionality, adapting to all types of spaces. With screw terminal connection, supports a maximum length of 30 meters and cabling wire section from 0.2 to 0.5 mm Made of thermoplastic materials, self-extinguishing and halogen-free, guarantees the security against possible to a fire, to prevent the flame spread and toxicity by smoke. Also, it has a temperature range of 5 ° C to 40 ° C and can reach temperatures that rocen the -25 and 50ºC. The Simon K45 mini jack connector, ensures maximum workplace solutions for audio, elegance and innovation, minimising the space and maximizing the functionality.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Female mini jack connector, wire cable tie and instruction sheet

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 30 meters For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 0,2 to 0,5 mm

CONNECTOR TYPE
Mini-Jack

NUMBER OF CONTACTS
3

NUMBER OF POSSIBLE ELEMENTS
1/2 element

FORMAT
Mini-Jack

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

RAL
9003

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

VERSION
Single

NUMBER OF WIRES
3

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION TYPE
Suitable for surface and flush mounting

REGULATIONS

REGULATIONS
Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436064751

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.02

PRODUCT NET WEIGHT
0.02

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436064751

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
50

PACKAGING WIDTH
40

PACKAGING LENGTH
50

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.012

PACKAGING VOLUME UNIT
HLT

PACKAGING GROSS WEIGHT
0.019

PACKAGING NET WEIGHT
0.02

PACKAGING WEIGHT UNIT
KGM