

Industrial bell 819 60-100W CCT 120°

REF. 81941038-787



BASIC INFORMATION

DESCRIPTION

Luminaire designed for industrial applications, suitable for high installations. High versatility thanks to its power and color temperature selector, allowing the luminaire to be adapted to each project with a single reference. Type of installation: Suspended. Optics: 120°. Color temperature: 3000 / 4000 / 5000K. Power: 60 - 80 - 100W. Lumens: 18000lm. Efficiency: 180lm/w. Protection grade IP: IP65. Power supply: 100-240 V. 50/60 Hz. Dimensions: 278 mm x 148 mm.

APPLICATION

General lighting for high ceilings, Industrial lighting

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IK CLASSIFICATION

09

IP RATING

IP65

OPERATING TEMPERATURE RANGE (°C)

-30...+45

POWER SUPPLY (V~)

100/240 V~

CONTROL

1-10 V

LIGHTING EFFICIENCY (LM/W)

180 lm/W

LUMENS (LM)

18000 lm

POWER (W)

60 - 80 - 100 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Suspension

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053440216

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

2.1

PRODUCT NET WEIGHT

1.53

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053440216

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

145

PACKAGING WIDTH

325

PACKAGING LENGTH

325

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

15315625

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

2.1

PACKAGING NET WEIGHT

1.53

PACKAGING WEIGHT UNIT

KGM