

Optical sensor 10m 110° wall surface KNX white IP20

REF. 89243743-330



BASIC INFORMATION

DESCRIPTION

Wall-mounted optical presence and light detector. The recommended installation height is 2.8 m, with a maximum height of 6 m. It has a detection angle of 110° and an opening angle of 110°. The tangential detection range is 10 m and the radial detection range is 10 m. The light regulation range is . The configuration of the detector is done via KNX. Possibility of interconnection between sensors. The control protocol is KNX. The power supply voltage is KNX (21-30 VDC). The operating temperature of the detector is: 0 - 40 °C. White finish, protection degree IP 20 and dimensions: 180 X 125 X 75 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

COMPATIBILITY

Simon Sensor Pro

TECHNICAL INFORMATION

IP RATING

IP20

RAL

9010

POWER SUPPLY (V~)

Bus KNX (21 Vcc...32 Vcc)

CONTROL

KNX

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.3

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053358177

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.391

PRODUCT NET WEIGHT

0.265

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053358177

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

75

PACKAGING WIDTH

125

PACKAGING LENGTH

180

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.391

PACKAGING NET WEIGHT

0.265

PACKAGING WEIGHT UNIT

KGM