

Customisable set with cover and brush, 2 schuko socket outlets and 3 empty elements white S400 Indesk

REF. 44502000-130



BASIC INFORMATION

DESCRIPTION

Kit within the table customizable with cover and brush strip, 2 sockets for Schuko plug and 3 empty elements, belonging to the series Simon 400 Indesk and finished in white colour. It can withstand heat of over 70 and has dimensions of 295 x 185 x 85 mm It can be installed by flush mounted in furniture and to fix it, you will have to use the claws that incorporates the kit or do so using screws in the holes available. The enclosure of this kit is made of painted steel, the profile in anodised aluminium and the covers and fastenings in self-extinguishing thermoplastic and halogen-free, which is a material that promotes a low level of toxicity and no flame spread in case of fire. Its maintenance is very simple as it just vas to have to wipe it with a soft and dry cloth and forget you for any type of a cloth or abrasive cleaner containing chlorine in its formula.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

ETIM CLASS

EC002759

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with brush

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

NUMBER OF POSSIBLE ELEMENTS

3

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9016

NUMBER OF REAR ENTRANCES

3

RECESS DIMENSION (MM)

273 x 175 mm (± 2mm)

NUMBER OF SOCKETS

2 sockets for standard current circuit

VERSION

5 elements

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLING ACCESS

With brush

CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

REMOVAL OF COMPONENTS

NUMBER OF COVER OPENING POSITIONS

1

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By lateral tightening of claws provided with the enclosure.

Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

Suitable for recessed mount in furniture.

OPENING ORIENTATION

At 45°

REMOVAL OF THE PLATE

Only with tool

SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD; Directiva 2011/65/UE RoHS; EN 50581:2012; EN 60670-1:2005; EN 60670-1:2005 A1:2013; IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053196397

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053196397

PACKAGING VOLUME

5836800

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

320

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

192

PACKAGING NET WEIGHT

1.85

UNITARY PACKAGING GROSS
WEIGHT

1.85

PACKAGING LENGTH

95

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

1.85