


Plastic bucket for adjustable floor box of 2 elements for installation on pavement floor Simon 500 Cima

REF. 52052101-035



BASIC INFORMATION

DESCRIPTION

The kit for shallow floor box of the series Simon 500 consists of 6 elements with 2 double Schuko plug and 2 plates for 1 RJ45 in a versatile grey colour. Its design for shallow floors allows it to be installed both in raised floor and concrete. If not installing the same floor lining of, this piece can be combined with the flush-mount trim cover. It measures 300x69 mm and it is manufactured with metal components with self-extinguishing, halogen-free thermoplastic insulation to ensure no flame propagation in case of fire and the low toxicity in case of smoke. It is fully compatible with elements up to 250 Volt voltage and 16 Ampere current and also allows the insertion by cutting (1 click ®). The constant effort of Simon by always offer the products most new and safe is materialize in its collection Simon 500 Cima, thanks to the fact that manages to assemble all types of mechanisms to convert homes of its customers in sites safer.

FINISH

Grey

PACKAGING CONTENTS

Tray and protective cover with installation manual

ETIM CLASS

EC000114

MATERIAL

Plastic

REMARKS

To complete the installation of the product, it must be combined with a concrete floor box for 2 elements in a grey (ref.52050001-035) or graphite finish (ref.52050001-038).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

AVAILABLE IN

2, 4, 6, 8 and 12 elements

IK CLASSIFICATION

08

NUMBER OF MODULES

2 modules

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

RECESS DIMENSION (MM)

220 x 172,2 mm

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

IP RATING

IP4X

NUMBER OF SIDE ENTRANCES

4

KIT AVAILABILITY

No

VERSION

2 elements

INSTALLATION AND MAINTENANCE

NUMBER OF CHANNEL ENTRIES

2

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING

Using screws

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Specially designed for installation in concrete floors

SCREWS REQUIRED FOR SLAB FIXING

Minimum 2 (1 per side, diagonally). It is recommended to fix the bowl with 4 screws for complete fixation.

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053101711

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053101711

PACKAGING VOLUME

3.45

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

75

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

200

PACKAGING NET WEIGHT

0.765

UNITARY PACKAGING GROSS
WEIGHT

0.765

PACKAGING LENGTH

230

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.765

