

Customisable table-top kit with 2xUSB charger, 2 German socket outlets and 1 empty element aluminium Simon 400

REF. 42422000-133



BASIC INFORMATION

FINISH

Aluminium

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INSULATION RESISTANCE (V-MΩ)

>5 M? at 500 V

RAL

9006

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

CURRENT (A)

16 A

NUMBER OF REAR ENTRANCES

1

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60❖C

IP RATING

IP30

NUMBER OF SOCKETS

2 sockets for standard current circuit

NUMBER OF POSSIBLE ELEMENTS

1

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

NUMBER OF USB CHARGERS

1

FORMAT

Schuko

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60❖ C

VERSION

4 elements

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

TYPE OF POWER SUPPLY CONNECTOR

Wieland❖ GST 18i male 3-pole overhead connector with 22 cm patch cord

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

SECURING POSSIBILITIES

Using clips included in the fastening brackets

REMOVAL OF COMPONENTS

INSTALLATION TYPE

Suitable for fixing to furniture.

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053208076

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053208076

PACKAGING VOLUME

2553125

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

215

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

125

PACKAGING NET WEIGHT

0.85

UNITARY PACKAGING GROSS WEIGHT

0.85

PACKAGING LENGTH

95

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.85