

Cover for German double socket outlet mechanism graphite Simon 500 Cima

REF. 50001041-038



BASIC INFORMATION

DESCRIPTION

Model of cover for mechanism of the double 50001041-038 socket outlet base of the Simon 500 Cima series. Element, with Viewer, without LED addressed to complete shots of running on different surfaces. Presents a design in graphite finishes and tones of colour. It is a piece of two modules for electrical installations that needs to be combined with a double Schuko socket outlet. It measures 100 x 50 x 9 mm and dimensions of depth of 9 mm, ideal for different environments. Manufactured with thermoplastic components, guaranteeing the relevant levels of security and protection In situations of fire and smoke. Element of quick and easy Assembly compatible with products of the Simon 500 Cima series, allows a Professional output of the Current closing of a professional electrical diagrams of all installation.

FINISH

Graphite

MATERIAL

Plastic

COMPATIBILITY

German double socket outlets
Simon 500 Cima

PACKAGING CONTENTS

Cover for mechanism of the
German double socket outlet
without viewer or LED light
indicator

ETIM CLASS

EC000011

REMARKS

Must be combined with a German double socket outlet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

Plate with viewer and LED light indicator, plate without viewer and as a replacement for plate with viewer

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C in surface-mount wall installation and +90 °C in flush-mount wall installation

FORMAT

Schuko

INDICATOR FUNCTION

No

IP RATING

IP20

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

NUMBER OF MODULES

2

RAL

7021

VERSION

2 elements

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

By direct snap-fit on the double socket outlet (no tools needed for fastening))

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface or flush-mount installation

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | IEC 60884-1 Ed. 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 | DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053254615

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.026

PRODUCT NET WEIGHT

0.026

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053093610

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

52

PACKAGING WIDTH

105

PACKAGING LENGTH

220

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1.201

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.26

PACKAGING WEIGHT UNIT

KGM

