simon

Touch LightKeypad button box 8 functions (4 channels and 4 scenarios) white Simon Scena

REF. 89000152-030



BASIC INFORMATION

FINISH

White

COMPATIBILITY

Touch Light Manager

PACKAGING CONTENTS

Touch LightKeypad, frame holder and instructions

ETIM CLASS

EC002466

REMARKS

Fitted with an IR input and compatible with SIMON 75350-69 remote control.



simon

TECHNICAL INFORMATION

BASIC CHARACTERISTICS

8 actions and everything off, 4 channels and 4 scenes.

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM NUMBER OF CHANNELS

1

TYPE OF MECHANISM

Requires connection to Touch Light Manager, Touch pulse

OPERATING TEMPERATURE RANGE (°C)

0 - 45 °C

OPERATION

8 actions plus off

POWER SUPPLY (V~)

12 VDC/DMX

SIGNALLING FUNCTION

Yes

STORAGE TEMPERATURE RANGE (°C)

0 - 45 °C

USE

Short press for On/Off

INSTALLATION AND MAINTENANCE

BUS CONNECTION TYPE OF TERMINAL CONNECTION

Por inserción

CABLE CHARACTERISTICS DATA

Multicore AWG 24; 2 shielded twisted pairs with impedance of 120 Ohms

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION TYPE

Semi-flush mount; requires universal flush-mount box.

REGULATIONS

REGULATIONS

UNE-EN 50491-3:2010 + 2004/108/CE + 2006/95/CE



simon

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053113004

UNITARY PACKAGING GROSS

WEIGHT

0.114

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING LENGTH

0

PRODUCT NET WEIGHT

0.114

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053113004

PACKAGING GROSS WEIGHT

0

PACKAGING HEIGHT

35

PACKAGING LENGTH

105

PACKAGING NET WEIGHT

0.114

UNITS CONTAINED PACKAGING

1

PACKAGING MEASUREMENT

UNIT MMT

PACKAGING VOLUME

0.441

PACKAGING VOLUME UNIT

DMQ

PACKAGING WEIGHT UNIT

KGM

PACKAGING WIDTH

120

