

Voice and data flat plate with dust cover for 1 element and 2 RJ45 connectors category 6 UTP white Simon K45

REF. KB96U/9



BASIC INFORMATION

DESCRIPTION

Model of plate for Voice and data connections number KB96U / 9 belonging to the range of professionals Simon K45 elements and components, with capacity for compatibilizar with other series of Elements of the same range. It is a plate of voice and Data of character diffuser, with dust cover for 1 element, designed for 2 category 6 UTP RJ45 connectors with snap-fit Keystone I, II, ATT ® / Avaya ® Integrated insertion tool. Presents all the approvals Of security professionals, thanks to its metal components with insulation Self-extinguishing halogen-free thermoplastic that guarantees no flame propagation In case of fire and low toxicity in the event of Smoke. Measures 45x45mm and a Depth of 30 mm, you need element 90 ° positioner (ref. K66) to guide the plate into a vertical position in caos of Systems vertical enclosures.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 6 UTP RJ45 connector and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RAL

9003

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Supplied with voice and data plate

CONNECTOR CHARACTERISTICS

Category 6 UTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

NUMBER OF MODULES

Half

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.035

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

1472064

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436032071

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.39

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

88

PACKAGING NET WEIGHT

0.35

UNITARY PACKAGING GROSS WEIGHT

0.035

PACKAGING WIDTH

123

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

136