
# Voice and data flat plate for 1 element without dust cover for 2 RJ45 compatible other manufacturers black Simon K45

REF. **KB076/14**



# BASIC INFORMATION

## DESCRIPTION

Element of plate for KB076 / 14 Connectors and voice and data connections, belonging to the range of professionals Simon K45 components, compatible with the different elements of the range Simon K45. Voice and data flat plate without Dust cover for one element for 2 RJ45 with snap-fit Keystone I, II, ATT ® / Avaya ®. Individual version of module means with colour And finishes in black, for the orientation of the plate it is recommended to use the 90º positioner (ref. K66). Maintains All the guarantees of security to integrate components of thermoplastic character Halogen-free; guarantees no flame propagation in case of Fire and low toxicity in the event of smoke generation. Its measures Are 45x45mm with a measure of depth of 8 mm, giving it a great versatility For different working environments professionals.

## FINISH

Black

## COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

## PACKAGING CONTENTS

Flat voice and data plate without dust cover

## ETIM CLASS

EC000018

## REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

## TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### COMPATIBLE WITH CONNECTORS
Simon®, ADC Krone® Series KM8 Keystone, AMP netconnect® Series SL110 and SL Tool less, BeldenCDT® Series Giga Flex Keystone, Ersys®, General Cable®, Molex®, Nexans® Series essential Keystone,Ortronics® Series Clarity TechChoice Keystone, Panduit® Series Netkey, R&M® Series Advance Cat6A (R509508, R509509), Rit®, Siemon® Series MAX Keystone, Systimax® and manufacturers of RJ45 with snap-fit based on the Keystone I and II format.

### RJ45 CONNECTORS
Not included in voice and data plate

### MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

### DUST PROTECTION
No

### FORMAT
RJ45

### IP RATING
IP20

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

### NUMBER OF MODULES
Half

### PLATE TYPE
Flat

### RAL
7021

### RJ45 ADAPTOR MODULE
Included in voice and data plate

### SNAP-FIT RJ45 PLATES
Keystone I, II, ATT®/Avaya®

### SNAP-FIT TYPE
Keystone I, II, ATT®/Avaya®

### VERSION
Single

## INSTALLATION AND MAINTENANCE

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

### INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

### INSTALLATION TYPE
Suitable for surface and flush mounting

### REMOVAL OF THE PLATE
Only with tool

## REGULATIONS

### REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

## LOGISTICS INFORMATION

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.011

### PRODUCT NET WEIGHT

0.011

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8426436065765

### UNITS CONTAINED PACKAGING

20

### PACKAGING HEIGHT

70

### PACKAGING WIDTH

93

### PACKAGING LENGTH

140

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

0.911

### PACKAGING VOLUME UNIT

DMQ

### PACKAGING GROSS WEIGHT

4.62

### PACKAGING NET WEIGHT

0.22

### PACKAGING WEIGHT UNIT

KGM