

2-way switch for card with 2 micro switch and light indicator 250V~ grey Simon 75

REF. 75550-35



BASIC INFORMATION

DESCRIPTION

This 2-way switch is suitable for cards and consists of 2 microswitches and a indicator light 6 A 250 V~. With grey finish, the mechanism consists of metal parts with halogen-free insulation and trim made of thermoplastic, a material known for its resistance to extreme temperatures, friction and knocks. It is advisable to install this 2-way switch in combination with a contactor / relay. This is not done, the maximum current of the 2-way switch is 6A (2A inductive). When to place the frame, the flanges of the frame should be broken. This control mechanism is included in the Simon 75 series, a collection that offers solutions suitable for all types of decorative spaces. To clean the 2-way switch, use a dry, soft textured cloth to avoid damaging the switch. Also, avoid cleaning products that are abrasive.

FINISH

Grey

COMPATIBILITY

Simon 75 frames

PACKAGING CONTENTS

Mechanism and cover

REMARKS

A contactor must be installed at the output of the mechanism. If this is not done, the maximum current of the switch is 10 A resistive (1.5 A inductive). It is recommended to protect the faston connectors with a heat shrink sleeve.

TECHNICAL INFORMATION

AVAILABLE MARKET CE	INDICATOR FUNCTION Yes	NOMINAL VOLTAGE (V~) 250 V~
CABLE SECTION ADMITTED (MM) 0,5 mm	CURRENT (A) 10 (1,5 ind.) A	OPERATING TEMPERATURE RANGE (°C) 5 - 40 °C
CONSUMPTION INDICATOR (MA) 1 mA	IP RATING IP20	POWER SUPPLY (V~) 250 V~
NUMBER OF POSSIBLE ELEMENTS 1 element	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	STORAGE TEMPERATURE RANGE (°C) -25 - 50 °C
FREQUENCY 50 Hz	TYPE OF MECHANISM Card	VERSION Single

INSTALLATION AND MAINTENANCE

CLAW Simon 27	INSTALLATION DIRECTION Horizontal, Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Faston
INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal	INSTALLATION TYPE Suitable for surface and flush mounting	

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN IEC 61058-1:2018 | EN 61058-1-1:2016 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
1517738

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
0.08

PRODUCT NET WEIGHT
0.08

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8421053048610

UNITS CONTAINED PACKAGING
5

PACKAGING HEIGHT
82

PACKAGING WIDTH
83

PACKAGING LENGTH
223

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
3017190

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.803

PACKAGING NET WEIGHT
0.4

PACKAGING WEIGHT UNIT
KGM