

2-way push-button switch with key 5A 250V~ (key removable in rest position) and welding terminal connection system white Simon 31

REF. 31520-30



BASIC INFORMATION

DESCRIPTION

2-way switch / push-button switch with white finish from the Simon 31 series with key removable in rest position and welded terminal connection. It works with a voltage of 250V and has a current of 5A. This mechanism is also equipped with 2 positions,. Supports a cable section of 0.5mm and can be located in places with a temperature of between 5 and 40°C, although it is capable of withstanding extreme temperatures of -25 to 50°C, approximately. It has been designed in accordance with standards UNE-EN 61058-1:2004 + A2:2008 and is manufactured with metal components with halogen-free thermoplastic insulation and thermoset trim. It measures 64x65 mm and cleaning this 2-way switch / push-button switch is very easy. You jsut need a soft cloth slightly moistened with soapy water, without having to use a cloth or abrasive cleaner with chlorine, to avoid damaging it.

FINISH

White

COMPATIBILITY

Simon 31 frames

PACKAGING CONTENTS

Mechanism with rocker

REMARKS

Mechanism with 2 positions and removable key in rest position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

NOMINAL VOLTAGE (V~)

250 V~

CABLE SECTION ADMITTED (MM)

0,5 mm

KEY-REMOVAL POSITION

Standby

OPERATING TEMPERATURE

RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE

(°C)

-25 - 50 °C

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Key

VERSION

Single

CURRENT (A)

5 A

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Welding

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN IEC 61058-1:2018 | EN 61058-1-1:2016 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.011

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

419050

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053006269

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

419050

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.011

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

58

PACKAGING NET WEIGHT

0.011

UNITARY PACKAGING GROSS

WEIGHT

0.011

PACKAGING WIDTH

85

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

85