

Downlight 800.21 White 15W 4000K

REF. 80021030-684



BASIC INFORMATION

APPLICATION

General technical lighting

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

COLOR TYPE

NW

IP RATING

IP54

CONTROL

On/Off

OPTICS

Extensive

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION
HEIGHT

80

TYPE OF TERMINAL
CONNECTION - FUNCTION 1

Quick connector

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053304426

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053304426

PACKAGING VOLUME

3272500

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

110

PACKAGING GROSS WEIGHT

0.426

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

170

PACKAGING NET WEIGHT

0.312

UNITARY PACKAGING GROSS
WEIGHT

0.312

PACKAGING LENGTH

175

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.312