

Angled voice and data plate with dust cover for 1 element with 2 RJ45 category 6 FTP aluminium Simon 500 Cima

REF. 50003086-033



BASIC INFORMATION

DESCRIPTION

To combine the most innovative design with the safest mechanisms and accessories is one of the features that makes it different from the angled voice and data plate with dust cover for an element with 2 RJ45 category 6 FTP connectors in aluminium colour of the Simon 500 Cima series compared to other similar products of the competition. Its dimensions are dimensions of 50 x 50 x 55,4 mm and has a cabling 22-24 AWG. This plate guarantees no flame propagation in case of fire and the low toxicity in case of smoke thanks to the metal components with self-extinguishing and halogen-free thermoplastic insulation. with which it has been designed. Also, this piece has two connectors RJ45 with snap-fit basic Keystone I, II, ATT / Avaya and includes clips for fastening in vertical and horizontal enclosures without the need for an adaptor at the best price.

FINISH

Aluminium

PACKAGING CONTENTS

Angled voice and data plate with dust cover, 2 RJ45 category 6 FTP and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Angled

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RJ45 ADAPTOR MODULE

Included in voice and data plate

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

CONNECTOR CHARACTERISTICS

category 6 FTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

2

VERSION

Single

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

54

UNITARY PACKAGING WIDTH

52

UNITARY PACKAGING LENGTH

215

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

603720

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.114

PRODUCT NET WEIGHT

0.114

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053097663

UNITS CONTAINED PACKAGING

20

PACKAGING HEIGHT

54

PACKAGING WIDTH

52

PACKAGING LENGTH

215

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.052

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

2.28

PACKAGING WEIGHT UNIT

KGM

