

Angled voice and data plate with dust cover for 1 element with 1 RJ45 category 6 UTP graphite Simon 500 Cima

REF. 50002081-038



BASIC INFORMATION

DESCRIPTION

Each day are more and more professionals in the sector of the electricity that include in its projects in new construction and refurbishment projects in homes, the angled voice and data plate with dust cover for an element with a RJ45 connector category 6 UTP in graphite finish of the Simon 500 Cima series. The resistance and functionality is one of the keys of this accessory that has dimensions of 50 x 50 x 42,5 mm and a cabling 22-24 AWG. This plate stands out for its easy maintenance, which translates into a long life span in time with its qualities as the first day. Metallic components with self-extinguishing and halogen-free thermoplastic insulation. make up its structure, which guarantees no flame propagation in case of fire and the low toxicity in case of smoke. Also, this product includes clips for fastening in vertical and horizontal enclosures without the need for an adaptor.

FINISH

Graphite

PACKAGING CONTENTS

Angled voice and data plate with dust cover, RJ45 connector category 6 UTP and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Angled

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RAL

7021

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

category 6 UTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

1

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097748

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.028

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

0.56

PRODUCT NET WEIGHT

0.028

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

