

Downlight 800.24 White 35W 3000K

REF. 80024030-283



BASIC INFORMATION

APPLICATION

General technical lighting

PACKAGING CONTENTS

1 Units

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

80

LUMENS/W

3400 lm/35W

IP RATING

IP54

ELECTRICAL CLASS

tipo 2

OPTICS

Extensive

OPERATING TEMPERATURE RANGE (°C)

-15°C a 35°C

L70 (°C)

50.000 h a 25°C

PHOTOBIOLOGICAL CLASSIFICATION

Categoría exento

POWER SUPPLY (V~)

220/240 V~

LIGHT BEAM APERTURE ANGLE (°)

60°

POWER (W)

35W

COLOR TEMPERATURE (K)

3000K

COLOR TYPE

WW

SERVICE LIFE

50.000 h

CONTROL

On/Off

LIGHTING EFFICIENCY (LM/W)

100 lm/W

COS Φ

0.95

LUMENS (LM)

3400 lm

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

130

INSTALLATION TYPE

Recessed

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50.000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053304532

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.974

PRODUCT NET WEIGHT

0.974

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053304532

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

145

PACKAGING WIDTH

250

PACKAGING LENGTH

215

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

7793750

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.192

PACKAGING NET WEIGHT

0.974

PACKAGING WEIGHT UNIT

KGM