

**Customisable kit with cover and fin, 2xUSB charger, 4  
schuko socket outlets and 1 empty element white S400  
Indesk**

REF. 45624000-130



## BASIC INFORMATION

### DESCRIPTION

Providing maximum safety in electrical systems is the reason for Simon's existence. In its 400 range, the customizable kit integrated into the table stands out, featuring a cover and fin, a 2xUSB charger, four schuko socket bases, and one empty element in white. With an intensity of 16 A and a voltage of 250 V~, it is suitable for flush mounting in furniture and compatible with all functions of the Simon 400 Indesk series. Among its most notable qualities are: insulation resistance of >5 MO at 500 V, Wieland® gst18i connector with three aerial male poles with a 22 cm patch cord and dielectric strength without drilling or contouring of 2000 V at 50 Hz for one minute. It has been manufactured with a painted steel casing, anodized aluminum profile, covers, and fixtures in self-extinguishing thermoplastic and halogen-free materials that ensure no flame propagation in the event of a fire and low toxicity in case of smoke emission.

### FINISH

White

### MATERIAL

Metal

### COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

### PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

### ETIM CLASS

EC002759

### REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with metal fin

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

### NUMBER OF POSSIBLE ELEMENTS

1

### FORMAT

Schuko

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### INSULATION RESISTANCE (V-MΩ)

>5 MΩ a 500 V

### CURRENT (A)

16 A

### IP RATING

IP30

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

### NOMINAL VOLTAGE (V~)

250 V~

### TYPE OF POWER SUPPLY CONNECTOR

Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL

9016

### NUMBER OF REAR ENTRANCES

1

### RECESS DIMENSION (MM)

318 x 175 mm (± 2mm)

### NUMBER OF SOCKETS

4 sockets for standard current circuit

### NUMBER OF USB CHARGERS

1

### VERSION

6 elements

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS

With metal fin

### CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

### NUMBER OF COVER OPENING POSITIONS

1

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING

By lateral tightening of claws provided with the enclosure.

Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

### REMOVAL OF THE FRAME

Only with tool

### INSTALLATION TYPE

Suitable for recessed mount in furniture.

### OPENING ORIENTATION

At 45°

### REMOVAL OF THE PLATE

Only with tool

### SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2014/30/UE EMC;Directiva 2011/65/UE RoHS;EN 50173-1:2011;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;EN 60950-1:2006;EN 60950-1:2006 A11:2009;EN 60950-1:2006 A1:2010;EN 60950-1:2006 A12:2011;EN 60950-1:2006 A2:2011\*3;ETSI-EN 301489-34 V1.4.1;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053273630

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

2.35

### PRODUCT NET WEIGHT

2.35

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053273630

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

90

### PACKAGING WIDTH

187

### PACKAGING LENGTH

340

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

5722200

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

2.35

### PACKAGING WEIGHT UNIT

KGM