

Flat voice and data plate without dust cover for 1 RJ45 Nexans® for 1 element graphite Simon 500 Cima

REF. 50018185-038



BASIC INFORMATION

DESCRIPTION

500 CIMA is the Simon series designed to provide solutions in any space professional for any type of connection has solutions for wall, by means of mechanisms to be recessed or surface-mounted; solutions for shallow floor, with or mini-towers; and solutions for open-plan areas or suspended ceilings. Always guaranteeing more high speed data transmission thanks to their plates category 6. As this plate for voice and data connections. With flat form and finished in graphite, it has an element and RJ45 connector Nexans ®. The plate also includes a snap-fit to be able to install it in wrappers horizontal or vertical, if the need for adapter. It measures 50x50 and with a depth of 11mm. This plate is made with thermoplastic components halogen-free, ensuring that the fire and the smoke is not propagate in case of fire. Simon always ahead of the functionality, design and security.

FINISH

Graphite

PACKAGING CONTENTS

Flat voice and data plate without dust cover

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

COMPATIBLE WITH CONNECTORS

Nexans® LANmark®-5 EVO, LANmark®-6 EVO.

RJ45 CONNECTORS

Not included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

DUST PROTECTION

No

FORMAT

RJ45

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

NUMBER OF MODULES

1

PLATE TYPE

Flat

RAL

7021

RJ45 ADAPTOR MODULE

Included in voice and data plate

SNAP-FIT RJ45 PLATES

RJ45 Nexans® connectors

SNAP-FIT TYPE

RJ45 Nexans® connectors

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053097052

PACKAGING VOLUME
0.604

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
10

PACKAGING VOLUME UNIT
DMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
54

PACKAGING GROSS WEIGHT
0

UNITARY PACKAGING GROSS
WEIGHT
0.025

PACKAGING WIDTH
52

PACKAGING NET WEIGHT
0.25

PRODUCT NET WEIGHT
0.025

PACKAGING LENGTH
215

PACKAGING WEIGHT UNIT
KGM

