

Blinds control module from 40 to 700W

REF. 89000203-039



BASIC INFORMATION

DESCRIPTION

This module is designed for the control of blinds, from 40 to 700 W is part of the series Simon Scena, which can be controlled, activating and deactivating all the functions from the touch screen of the virtual tool that is included with this collection. Thanks to the two auxiliary inputs that has, enables the operation as regulator of the blind. Also makes it possible to program a percentage of adjustment (0 to 100%), has the function of locked of trunking and also allows the self-calibration of the blind. A luxury in terms of functionality. A luxury in terms of comfort. The life of the user who has Simon Scena will be easier to always. In addition, you can control the operation of a blind with a power of 40 to 700 W before purchasing this product, and to install it, you should know that the direction of installation of this product Scena must be in DIN rail. The code of this product is the following: 89000203-039.

COMPATIBILITY

Blinds

PACKAGING CONTENTS

Blinds control module and instructions

ETIM CLASS

EC001330

REMARKS

Can function as an independent blind regulator for Scena thanks to its two auxiliary inputs.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

OPERATION

Dimming

BASIC CHARACTERISTICS

Controls operation of blinds with a power of 50 to 700W and has two push-button auxiliary inputs.

MAXIMUM NUMBER OF CHANNELS

1

POWER CABLE SECTION (MM²)

1.5 mm

PUSH BUTTON INPUT FOR CONTROL WITHOUT CONSOLE

Yes

TYPE OF MECHANISM

With Scena and/or auxiliary inputs in stand-alone mode

POWER RANGE (KW)

50-700 W

POWER SUPPLY (V~)

127/230 V~

FREQUENCY

50 - 60 Hz

OPERATING TEMPERATURE RANGE (°C)

0 - 45 °C

STORAGE TEMPERATURE RANGE (°C)

0 - 45 °C

INSTALLATION AND MAINTENANCE

BUS CONNECTION TYPE OF TERMINAL CONNECTION

Por inserción

CABLE CHARACTERISTICS DATA

Multicore AWG 24; 2 shielded twisted pairs with impedance of 120 Ohms

INSTALLATION DIRECTION

DIN rail

INSTALLATION TYPE

DIN rail or false ceiling.

REGULATIONS

REGULATIONS

UNE-EN 50491-3:2010 + 2004/108/CE + 2006/95/CE

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053096482

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.138

PRODUCT NET WEIGHT

0.138

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053096482

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

40

PACKAGING WIDTH

110

PACKAGING LENGTH

120

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.528

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.138

PACKAGING WEIGHT UNIT

KGM