Extension 1.5 metres for aluminium column with 4 sides Simon K45

REF. **ALK54P15/8**



BASIC INFORMATION

DESCRIPTION

Only expand the workplace solutions of their work area with the extension of 1.5 metres for pole 4-sided within the collection Simon K45 made in anodised aluminium for greater resistance and durability of the product, it is advisable to combine one extension per pole to ensure the robustness of the product. With a size of 1500 x 125 x 125 mm, the extension of the K45 range, you can get to reach temperatures in installation of -25ºC and most of 120 ° C, exceeding the 120 ° C in construction. For Simon K45, the rank is give your work area the greater workplace solutions, functionality and innovation through designs that adapt perfectly in spaces compact. Once again, Simon K45 offers you the maximum functionality in the minimum space.

FINISH

Metal

COMPATIBILITY

Simon K45 functions

ETIM CLASS

EC000795

MATERIAL

Aluminium

PACKAGING CONTENTS

Column extension, front cover, connecting pins and screws

REMARKS

To ensure the robustness of the unit, it is only possible to combine one extension per column.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

AVAILABLE IN
2-sided (square and oval) and 4-sided

DIELECTRIC STRENGTH
Without perforation or contournament with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (ºC)
+120º C

EARTHING RESISTANCE
< 0.05 ?

ELECTRICAL PROPERTIES
With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING
Separation by means of the compartments of the extension itself to eliminate any possible electromagnetic interference and transmission errors between the electric cables and Voice, Data and Multimedia.

HEAT RESISTANCE (ºC)
+650ºC (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)
5 MOhms at 500 V.

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (ºC)
-25 a 120º C

VERSION
4-sided

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

REMOVAL OF COVER
Only with tool

TYPE OF FASTENING
Using connecting pins

INSTALLATION DIRECTION
Vertical

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436050624

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
7.8

PRODUCT NET WEIGHT
7.8

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436050624

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
119

PACKAGING WIDTH
139

PACKAGING LENGTH
1503

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
24.861

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
7.8

PACKAGING NET WEIGHT
7.8

PACKAGING WEIGHT UNIT
KGM