Bipolar thermal-magnetic circuit breaker 10A with 1 double element trim plate and 42 mm height graphite Simon Cima

REF. **S195S/14**



BASIC INFORMATION

FINISH

Graphite

COMPATIBILITY

With Simon Cima Pro surface-mounted and flush wall boxes, Cima Classic flush wall boxes with 33mm housing, adjustable and shallow depth floor boxes, and PVC cable guide trunking.

ETIM CLASS

EC000042

TECHNICAL INFORMATION

BREAKING CAPACITY (A)
6000 A

CURRENT (A)
10 A

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

POWER SUPPLY (V~)
400 V~

RAL
7021

TRIP CURVE
C Curve

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
10

INSTALLATION DIRECTION
Horizontal, Vertical

REMOVAL OF THE MCB
Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436024038

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
753878

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.334

PRODUCT NET WEIGHT
0.334

UNITARY PACKAGING WEIGHT UNIT
KGM

UNITS CONTAINED PACKAGING
5

PACKAGING HEIGHT
118

PACKAGING WIDTH
121

PACKAGING LENGTH
264

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3769392

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
1.67

PACKAGING NET WEIGHT
1.67

PACKAGING WEIGHT UNIT
KGM