

Spotlight 640.10 Flush mount NW CRI 80 Spot Black

REF. 64010038-284



BASIC INFORMATION

DESCRIPTION

Simon works constantly to find the best installation solutions in lighting and electricity. Complies with the strictest national and international regulation and subjects its products to permanent review. Not only to improve its appearance and contribute to the design of the best alternative but to solve all the problems that can be presented in the installations. The line of 640 spotlights, which can be flush mounted or placed on three-phase rails, due to its versatility and minimalist design, provide new forms of indoor lighting. In the case of the Spot range, that allows us to direct the light, sending it downwards in a beam of 15 °. The specific lighting of products or special elements is guaranteed. This is a luminaire for indoor lighting. Dichroic filters can also be incorporated by replacing the normal protective glass. The dichroic filters are responsible for letting a range of colour, according to the lighting needs. A 640 Spotlight Flush-mounted Amber SPOT Black. Category B Colour temperature Amber 2500 K. SPOT. Light intensity 2100 lm / 23 W. Durability 30,000 h at 25 ° C. 120-240 V 50 / 60 Hz. ON-OFF switching system. Supports up to 35 ° maximum. Weight 1.4 kg 100x102 mm dimensions For flush mounting.

APPLICATION

Accent lighting, General lighting

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DIRECTIONAL

Yes

LUMENS (LM)

2600 lm

IP RATING

IP20

DRIVER INCLUDED

Yes

LUMENS/W

2600 lm/30W

OPERATING TEMPERATURE RANGE (°C)

35 °C maximum

ELECTRICAL CLASS

Type 1

OPTICS

Spot

POWER SUPPLY (V~)

120/240 V~

L70 (°C)

100,000 h at 25° C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

4000 K

L90 (°C)

30,000 h at 25 °C

POWER (W)

30 W

CONTROL

On/Off

COLOR TYPE

NW

SERVICE LIFE

50.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

87 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Flush mount

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053137949

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.4

PRODUCT NET WEIGHT

1.184

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053137949

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

160

PACKAGING WIDTH

200

PACKAGING LENGTH

250

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

8000000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.4

PACKAGING NET WEIGHT

1.184

PACKAGING WEIGHT UNIT

KGM